

CAVIUS


WIRELESS
ALARM FAMILY
SMOKE
ALARM




DANISH
DESIGN



10 YEAR
BATTERY



100%
TESTED



WIRELESS
ALARM FAMILY

SMOKE
ALARM





CAVIUS

PRODUCT TYPE: OPTICAL SMOKE ALARM DEVICE WITH WIRELESS INTERLINK

PRODUCT NUMBER: 2106-001

PRODUCT DATA:

SMOKE ALARM TYPE:

Optical smoke alarm device with wireless interlink

USAGE:

Designed for installation in private homes, camping trailers, mobile homes and caravans. Not recommended for boats.

The alarm can be connected with other alarms from the Cavius Wireless alarm family.

ISOTOPE ACTIVITY:

Absence of radioactive substances

OPERATION AC/DC:

DC

BATTERY TYPE:

Non-replaceable 10 year battery (pack of 2 CR123A Lithium batteries)

POWER CONSUMPTION:

Battery consumption is 162mAh for one year in normal operation

BATTERY LIFE:

Minimum 10 year life in normal operating condition (Based on a weekly testing)

INTERLINK FREQUENCY:

868MHZ

RANGE:

Minimum 100m in open field. Range depends on the building materials and will need to be tested in each individual case.

LOW BATTERY INDICATION:

A short acoustic "beep" will sound and LED flash every 48 seconds when the voltage is below 2.85V. In this stage it will continue for minimum 30 days, and can drive the alarm for 4 minutes.

NORMAL OPERATION:

LED flashes every 48 second for normal operation

SOUND:

Audible indicator min. 85 dB @ 3 meter in anechoic chamber

SOUND PATTERN:

Fire alarm condition is indicated by a series of three successive tones

VISIBLE INDICATOR:

A red LED is used to indicate the following conditions:

- fire alarm condition is indicated by a flash every 0.5 seconds
- smoke sense speed up is indicated by a flash every 2 seconds when the smoke level is at the alarm threshold
- normal operation is indicated by a flash every 48 seconds

PUSH BUTTON:

The smoke alarm includes a push button switch built into the top of the alarm for easy access. This button has the following functions:

- set up - Press the button to start sending out a specific house code to the others alarms
- hush – during an alarm condition this immediately silences the alarm when pressed. When the button is released, the alarm remains silenced for 10 minutes
- test – when not in alarm the sounder can be activated to provide a sensor OK test function. While the button is pressed, the audible and visible indicators are activated if the sensor is OK

WARRANTY:

10 year

PRODUCT WEIGHT (GR):

Base alarm weight (excluding screws, plugs and mounting ring): 96 g



PRODUCT TYPE: OPTICAL SMOKE ALARM DEVICE WITH WIRELESS INTERLINK

PRODUCT NUMBER: 2106-001

PRODUCT DATA:

OPERATING TEMPERATURE:

+4°C to +38°C (tested from 0 degrees to 55 degrees)

OPERATING HUMIDITY:

Up to 90% RH non-condensing

DETECTION TIMING:

The alarm makes an optical reading every 8 seconds. At unusual readings (going into alarm stage), the readings are taken every 2 seconds.

INSTALLATION POSITIONS:

Wall & ceiling. Set of 2 x screws and 2 x plugs included

APPROVALS:

EN 14604:2005 + AC :2008
EN60065
EN300-220
ROHS
REACH

CE TESTING INSTITUTE:

CNPP

NOTIFIED BODY:

AFNOR Certification

ADDITIONAL TESTING AND APPROVALS:

SGS (RF approval)

ASSOCIATIONS:

Cavius is member of GIFSID, manufacturers association of domestic fire safety equipment

STORAGE TEMPERATURE:

-20°C to +60°C

STORAGE HUMIDITY:

Up to 93% RH non-condensing

QUALITY ASSURANCE:

SOUND LEVEL:

100% tested in special designed sound chamber

SENSITIVITY:

100% tested in special designed test tunnel made by world leader AWT (UK)

POWER CONSUMPTION:

100% tested

BATTERY VOLTAGE AND INTERNAL RESISTANCE:

100% tested

ALARM FUNCTION:

100% tested

INTERCONNECTION:

100% tested

VISUAL APPEARANCE:

100% tested

PACKING CONTENT:

100% tested

CONTACT


www.cavius.com

MANUFACTURER

Manufacturer: Cavius Aps, DK8600

CAVIUS

WIRELESS
ALARM FAMILY



Diameter: 78 mm

DISTRIBUTOR: